

# Introduction

- Mirza S Altaf Hussain, CPP, MBA, NEBOSH-IGC
  - Active member of ASIS Dubai Chapter 250 since 2011
  - CPP Trainer for ASIS Dubai Chapter 250
  - Executive Committee Member since 2013
  - Young Professional Liaison since 2013




# Guidelines and Rationale for Physical Security Counter-measure Placement within an Educational Setting

Focus on the principles behind designing a layered system of security counter-measures which can be applied in an educational environment



# ADEC Guidelines for Private Schools

- Abu Dhabi Education Council (ADEC) recommend to use IP technologies
- ADEC policy 5210 focuses on Security Video Surveillance System (CCTV) with following in mind:
  - Enhance Security
  - Respect privacy
  - Control access to recordings



مجلس أبوظبي للتعليم  
Abu Dhabi Education Council  
التعليم أولاً Education First

**Bicsi**

# Purpose for CCTV

- Promote a safe learning environment.
- Increase personal safety of students, staff and visitors.
- Deter and detect crime, vandalism, unlawful behavior and inappropriate conduct.
- Protect school buildings and their assets.



# ADEC Suggested Locations For Cameras

- Promote a safe learning environment.
- All entrances and exits of building and school grounds.
- All walkways and public areas (corridors, stairs, courtyard, sports areas, canteen).
- Learning Resource Center (libraries).
- Student pickup and drop-off areas (private vehicle and bus).
- Security areas and hazardous areas (control room).
- Exterior areas surrounding the school grounds.
- Cameras shall not be installed in classrooms and lavatories.



# ADEC Suggested Locations For Cameras



S/N	Location	Observation Criteria	Surveillance Requirements
1	Student Pick up & Drop off	Recognize	Vehicle Number Plate, type and color of vehicle, passenger and overview of surrounding area.  Fixed cameras  PTZ cameras required for general surveillance
2	Landscape	Detect	Landscape cameras shall cover the school perimeter.
3	Main Entrance & Lobby		
a	Main entrance	Identify	Both entry and exit view Fixed cameras(WDR & IR)
b	Reception lobbies	Recognize	Fixed cameras and PTZ cameras for general surveillance
c	Cashier	Identify	Front view of the customer and transaction. Complete view of the counter with no dead zones. - Fixed cameras

# ADEC Suggested Locations For Cameras



<b>4</b>	<b>Other Building Access points</b>		
a	Access points to all school buildings	Recognize	Entry & Exit view - Fixed cameras(WDR & IR)
<b>5</b>	<b>Elevator Lobbies</b>		
a	Elevator lobbies in BOH, FOH and Car park where entry & exit from building is possible	Recognize	People entering and exiting elevators – Fixed cameras
<b>6</b>	<b>Circulation Corridor</b>		
a	Circulation corridor on all floors	Recognize	Fixed cameras
<b>7</b>	<b>Emergency Exit</b>		
a	Emergency exits on all school buildings where entry & exit from building is possible	Identify	Entry or exit view based on the direction of emergency exit Fixed cameras(WDR & IR)



# ADEC Suggested Locations For Cameras



<b>8</b>	<b>Staircases</b>		
a	Staircase on all floors	Recognize	
<b>9</b>	<b>Canteen</b>		
a	All canteen entries	Recognize	Fixed cameras
b	Kitchen entry/exits	Recognize	Fixed cameras(WDR & IR)
c	Canteen Dining Area		PTZ camera for general surveillance
d	Food delivery and storage areas	Recognize	Entry View - Fixed cameras
e	Cashier	Recognize	Fixed camera
<b>10</b>	<b>Chemical Labs</b>	Recognize	
<b>11</b>	<b>Auditoriums/Ground / Play areas / Sports Hall /Swimming Pool</b>	Recognize	
<b>12</b>	<b>Entrances to Janitor room/ Wash rooms / Stores</b>	Recognize	
<b>13</b>	<b>Inside school buses</b>	Recognize	Minimum 3 fixed camera (WDR & IR) to cover the whole bus seating area. All video shall be recorded at 4 CIF/6.25 FPS
<b>14</b>	<b>All outdoor cameras</b>		Shall be with IR illuminator (Min.30 Meter)



# ADEC Suggested Locations For Monitors

- They shall be installed in the office of the Principal and Vice Principal.
- In security office for the purpose of monitoring the facility outside of school hours and overnight.
- Male security guards shall not have access to viewing CCTV footage of girls' schools during the school day.



# ACCESS to Recording

- Principal and Vice Principal are authorized to view and retrieve the recordings.
- CCTV recordings of female students and staff shall be monitored by female Principals and Vice Principals only.
- All other school-based staff members are strictly prohibited from accessing recordings.



# ADEC's Suggestions on Recording

- Retained for a period of 180 days at 12-30 FPS.
- System shall support MJPEG/MPEG4/H.264 compressions
- System shall have capacity of 25% expansion
- Redundancy at min. RAID5 with hot standby HDs such as failure of system shall not affect overall system as well as automatic redistribution of cameras
- Record should have camera#, location, date/time stamp
- All systems should be time synchronized such as IDS, Access control, CCTV etc.



# ADEC's Suggestions on Recording

- Retained for a period of 180 days at 12FPS.
- If incident captured in a recording that requires clarification beyond the school level, Cluster Manager shall coordinate with the Executive Director of ADEC
- No copy of any recordings may be shared with any person or entity unless upon a judicial order or by prior written approval of the Executive Director of ADEC School Operations.
- Duplication or distribution of recordings is strictly prohibited and punishable by law . School is responsible to maintain confidentiality of CCTV recordings.



# ADEC's Suggestions on Recording

- System must have 3 types of recordings:
  - Motion
  - Continuous
  - Video analytic
- End-user must have access to live footage anywhere in the premises on network.



# ADEC's Suggestions on Cameras

- IP camera with H.264 encoding and security features of HTIPS & 802.1x
- Camera must support resolution from CIF to 4CIF/HD
- I-frame rate shall be at least one I-frame once every 1-4 sec.
- Indoor camera: Color camera with 20 Lux illumination
- Outdoor camera: Camera with IR cut filter
- Area with variation in lighting condition: WDR cameras (with 120db)





# ADEC's Suggestions on Cameras

- Camera/encoder streams shall be streamed as transport RTP/UDP
- VMS shall support multicast streaming
- Camera/encoders shall be synchronized with GPS time
- Analog camera: min. resolution of 540 TVL
- Any camera selection should be depended on observation criteria



# ADEC's Suggestions on Observation Criteria

- Four categories of Observation Criteria based on relative size of 1.6m tall person appearing on monitor:
  - Monitor & Control
  - Detect
  - Recognize
  - Identify



# ADEC's Suggestions on Monitoring and Control Room

- Operator shall be trained on event response
- Resolution of monitors shall exceed the highest resolutions camera used
- # of monitors will depend on # of cameras and integration with other systems
- Alarms integrations shall alert visually as well as audibly
- Max. 9 camera's view on screen of 17"-21" monitor



# ADEC's Suggestions on Lighting

- Max. to min illumination ratio available in the field of view shall be better than 4:1
- IR illuminators shall be provided, where lighting conditions can not be maintained
- Following conditions should be considered before selecting camera, location and lighting:
  - Back lighting
  - Glare
  - Poor/no lighting



# ADEC's Suggestions on Transmission

- Design shall support video delivery with min. delay, loss and jitter
- Design shall provide end to end security, limiting unauthorized access
- Shared transmission network is not recommended
- All switches shall have 1+1 redundant power supply and cooling fans
- School is responsible for performance of system:
  - Network availability
  - Network security
  - Bandwidth availability
  - Maintaining source image quality
  - Min. Latency (Inline with manufacturer's limit)



# ADEC's Suggestions on Network switches/firewall

- VMS shall be compatible with MCC provided IP scheme
- If school uses multicast routing, routing shall be based on PIM-SM
- Core level switches (layer-3) must be redundant in nature with 2 physical core switches
- Four core single mode fiber connectivity from equipment rack for integration to Etisalat POP room
- Firewall shall be default gateway for VMS





# ADEC's Suggestions on VMS

- VMS shall have failsafe mode (For automatic NVR switchover)
- VMS shall support multicast streaming (ICD-Interface control document)
- VMS shall allow connection to other systems through WAN/LAN
- VMS shall allow realtime and recorded video stream, in non-encrypted RTP/UDP protocol
- VMS shall support the recommended compressions



## ADEC's Suggestions on servers

- Servers shall have failsafe mode (For automatic server switchover)
- Servers load shall not exceed an average of 70%
- Server shall have dual processors, dual powers and min. 1Gbps dual communication uplinks to network



# ADEC's Suggestions on Storage

- Storage shall have min. RAID 5 or above configured
- HD shall have min. level of 7200rpm
- Storage shall have dual processors, dual powers and dual network uplinks to NAS/SAN switches
- Min. of 20TB storage



# ADEC's Suggestions on Alarm logs

- Alarms logs for all events:
- For cabinet open/close
  - Loss of system communication
  - Loss of camera signal
  - System power down
- 180 days of logs shall be available



# ADEC's Suggestions on CCTV installation

- Install on inaccessible height
- Camera on accessible height shall be vandal proof
- Outdoor camera with IP65 rated enclosures, sun shade and cooling mechanism
- All equipments shall be kept in lockable cabinets



# ADEC's Suggestions on Power

- CCTV system shall be on additional UPS backup of min. 15mins , provided generator will start within 10mins of power failure
- CCTV system shall be on additional UPS backup of min. 2hrs , if generator are not available or they are not guaranteed in case of power failure
- System shall restart automatically without human interaction
- Power distribution shall be from secured location





# ADEC's Suggestions on Maintenance

- On call response time shall not exceed 2hrs
- Maintain log for all maintenance and stoppage
- Quarterly maintenance shall include:
  - Inspection & confirmation on correct operations
  - Full system tests to evaluate performance
  - Inspection of field devices & cleaning
  - Rectification and reporting of any condition



# ADEC's Suggestions on Training

- School shall train following:
  - Operators on event response
  - Maintenance team on maintenance of system
  - Two representative on video review, export and system health check
- School shall maintain following credentials:
  - Training certificates
  - Qualifications
  - Past employment history



# ADEC's Suggestions on Documentation

- School shall maintain following documentations:
  - Maintenance contract
  - Trade lincense
  - As built drawings
  - Maintenance manuals
  - Operational manuals
  - List of people having access to videos
  - Risk assessment report
  - Site plan with camera icons and identification numbers



# ADEC's Suggestions on Signage

- School shall place signage in Arabic and English languages with camera icon stating following:  
“CCTV cameras in operation”



# **ADEC's recommendations on location, surveillance and observation criteria**

- School shall carry out their own risk assessment, before installation
- School shall budget in phases to cover whole building from fences, gates, entrances to all internal areas.
- School may approach approved vendors only



# Educational setting

- School shall carry out their own risk assessment, before installation to find the level of countermeasures needed
- Most of the school do not need systems more than:
  - Locks
  - Keypads & electronics locks
  - PAS system
  - CCTV





# Educational setting

- School shall find the level of countermeasures needed
  - Detect
  - Deter
  - Deny
  - Destroy
- No system/machine can guarantee 100% security, without focusing on man and method.
- School should find the right balance in their efforts to ensure security.



**Thank you.**

**Please feel free to ask any question.**



***Bicsi***